

(12) UK Patent Application (19) GB (11) 2 359 139 (13) A

(43) Date of Printing by UK Office 15.08.2001

(21) Application No 0104417.1

(22) Date of Filing 15.06.2000

(30) Priority Data

(31) 9913935.4 (32) 15.06.1999 (33) GB

(86) International Application Data
PCT/GB00/02329 En 15.06.2000

(87) International Publication Data
WO00/77480 En 21.12.2000

(51) INT CL⁷
G01F 23/00 23/36

(52) UK CL (Edition S)
G1N NAEC N1D3 N7G N7N

(56) Documents Cited by ISA
EP 0378402 A1 EP 0295609 A1 US 5421193 A
US 4723446 A

(58) Field of Search by ISA
INT CL⁷ G01F
EPO-internal, WPI data, PAJ

(71) Applicant(s)
Scientific Generics Limited
(Incorporated in the United Kingdom)
Harston Mill, HARSTON, Cambridgeshire, CB2 5GG,
United Kingdom


(72) cont
Andrew James White
Victoria Ann Clark

(72) Inventor(s)
Richard Alan Doyle
Euan Morrison

(74) Agent and/or Address for Service
Beresford & Co
2/5 Warwick Court, High Holborn, LONDON,
WC1R 5DH, United Kingdom

(54) Abstract Title
Position encoder

(57) A linear position sensor is provided which employs phase quadrature sensor windings, an excitation winding and a resonator. When an excitation current is applied to the excitation winding, it causes the resonator to resonate which in turn induces signals in the sensor windings. The sensor windings are spatially arranged so that the electromagnetic coupling between them and the resonator varies with the position of the resonator. The excitation windings, phase quadrature windings and resonant circuit are arranged so that the magnetic fields involved in the operation of the position sensor are substantially parallel to each other and the direction of movement of the resonator. Consequently, the effect of rotation of the resonator or lateral movement of it relative to the excitation and phase quadrature windings is alleviated.



GB 2 359 139 A